ELATION
PROFESSIONAL

FUZE
SERIES

THE IDEAL FUSION OF PERFORMANCE, FEATURES AND VALUE

FUZE
PROFILE

FUZE
PROFILE CW

FUZE
SPOT

FUZE
SFX

FUZE
MAX PROFILE

Including
Snoot

FUZE
MAX SPOT

Including
Snoot

FUZE
WASH 500

Optional
4-Leaf Motorized Barndoor
for FUZE WASH 500

Optional
Indexable Ovalizer Lens
for FUZE WASH 500

FUZE
WASH FR

FULL SPECTRUM

The Fuze Spot and Fuze Profile with framing house powerful full-color-spectrum RGBMA color mixing engines that offer a high CRI and wide color gamut. Full featured with a strong, flat field performance, the Fuze Spot and Profile are the perfect combination for a variety of stage applications.

AUTOMATED ELLIPSOIDAL

The Fuze Profile CW with cold white LED engine, framing, dual color wheels and gobos is ideal for exhibition, corporate event and broadcast lighting solutions. Housing a 380W 91 CRI White LED engine that ensures accurate color reproduction, it provides a clean, flat-field keylight and can be used anywhere a fully automated ellipsoidal fixture is required.

SUPERIOR WASH

The Fuze Wash FR features a 480W RGBMA LED engine offering an extremely high CRI and full-spectrum color engine calibrated and optimized for use with the Fuze Profile and Spot. It features a specially designed Fresnel lens optical design, providing a smooth and even wash, motorized zoom and an internal full blackout framing system for beam control and effects.

SPOT EFFECTS

Designed as a compact yet powerful multi-functional spot, beam and FX moving head, the Fuze SFX features a remarkably bright 300W white LED engine with CMY color mixing system. Designed as the ultimate spot and effects fixture providing narrow beam angles to wide zoom coverage, it is loaded with features and new FX system for endless combinations and truly spectacular looks.

FEATURES, PERFORMANCE AND VALUE TO THE MAX!

The Fuze MAX is a 21,000-lumen full-spectrum LED moving head with RGBMA LED engine (92 CRI) that rivals 1000W/1200W class discharge fixtures. Available in Spot and Profile framing versions, the Fuze MAX has been designed for precision lighting applications such as theater, broadcast and Houses of Worship where a wider chromatic spectrum (including dynamic whites), a full feature set and outstanding quality is required.

AUTOMATED FRESNEL

The Fuze Wash 500™ is a full-spectrum LED Fresnel moving head fixture designed for theater, television, events and a wide array of other precision lighting applications. It houses a 500W RGBMA LED engine and delivers a powerful output of up to 17,000 lumens with CRI of 92. It is designed for any application where an automated Fresnel fixture with outstanding and impactful colors, a wide zoom range and a soft field of light is required.

Specifications subject to change without notice

Product Overview

FUZE SPOT

SOURCE
- 305W 6,500K RGBMA LED Engine
- 30,000 Hour Average LED Life*

PHOTOMETRIC DATA
- 10,100+ Total Lumen Output
- CRI 94+

EFFECTS
- 7° - 42° Motorized Zoom
- Variable Frost Filter
- 4 Facet Prism
- Motorized Iris
- Variable 16-bit Dimming Curve Modes

GOBOS
- 2x 6 Rotating / Indexing Interchangeable Glass Gobos
- Animation Wheel

CONTROL / CONNECTIONS
- 4 DMX Channel Modes
- 16-bit Pan, Tilt, and Dimming Control
- DMX Adjustable LED Frequency
- DMX, RDM Protocol Support
- Locking 5pin XLR In/Out
- Locking Power In/Out

SIZE / WEIGHT
- LxWxH: 407 x 256 x 698 mm (16.0" x 10.1 x 27.4")
- Weight: 21 kg (46.3 lbs.)

FUZE SFX

SOURCE
- 300W 6,600K White LED Engine
- CMY Variable Color Mix

PHOTOMETRIC DATA
- 12,000+ Total Lumen Output
- CRI 68+ (CRI 84 with High CRI Filter)

EFFECTS
- 4.5° - 38° Motorized Zoom
- Remote Focus
- Variable Frost Filter
- Dual Independent Prisms for Layering
- Motorized Iris

GOBOS
- Rotating Gobo Wheel with 8 Interchangeable Glass Gobos
- Fixed Gobo Wheel with 10 Gobos

CONTROL / CONNECTIONS
- 31 DMX Channel Modes
- 16-bit Pan, Tilt, and Dimming Control
- DMX, RDM, Art-NET, and sACN Protocol Support
- Locking 5pin XLR In/Out
- Locking RJ45 Ethernet In/Out

SIZE / WEIGHT
- LxWxH: 370 x 230 x 600 mm (14.6" x 10.1" x 23.6")
- Weight: 19.3 kg (46.3 lbs.)

FUZE PROFILE

SOURCE
- 305W 6,500K RGBMA LED Engine
- 30,000 Hour Average LED Life*

PHOTOMETRIC DATA
- 10,100+ Total Lumen Output
- CRI 94+

EFFECTS
- 7° - 42° Motorized Zoom
- 4 Rotating Full Blackout Framing Blades, +/- 45 Index
- Variable Frost Filter
- 4 Facet Prism
- Motorized Iris
- Variable 16-bit Dimming Curve Modes

GOBOS
- 1x 6 Rotating / Indexing Glass Gobos, 1x 7 Fixed Glass
- Animation Wheel

CONTROL / CONNECTIONS
- 4 DMX Channel Modes
- 16-bit Pan, Tilt, and Dimming Control
- DMX Adjustable LED Frequency
- DMX, RDM Protocol Support
- Locking 5pin XLR In/Out
- Locking Power In/Out

SIZE / WEIGHT
- LxWxH: 407 x 256 x 698 mm (16.0" x 10.1 x 27.4")
- Weight: 25 kg (55.1 lbs.)

FUZE PROFILE CW

SOURCE
- 380W 6,000K White LED Engine
- 30,000 Hour Average LED Life*

PHOTOMETRIC DATA
- 11,200 Total Lumen Output
- CRI 91+

EFFECTS
- 9° - 43° Motorized Zoom
- 4 Rotating Full Blackout Framing Blades, +/- 45 Index
- Motorized Iris
- Variable 16-bit Dimming Curve Modes

GOBOS
- 1 Gobo Wheel
- 7 Rotating / Indexing Interchangeable Glass Gobos

CONTROL / CONNECTIONS
- 2 DMX Channel Modes
- 16-bit Pan, Tilt, and Dimming Control
- Motorized Focus
- DMX, RDM Protocol Support
- Locking 5pin XLR In/Out
- Locking Power In/Out

SIZE / WEIGHT
- LxWxH: 408 x 252 x 698 mm (15.9" x 9.9" x 27.4")
- Weight: 23.3 kg (51.4 lbs.)

FUZE MAX SPOT

SOURCE
- 800W 6,500K RGBMA LED Engine
- 30,000 Hour Average LED Life*

PHOTOMETRIC DATA
- 21,000 Total Lumen Output
- CRI 93+

EFFECTS
- 7° - 53° Motorized Zoom
- Dual Variable Frost Filter (Medium/ Wash)
- 4 Facet Round, 4 Facet Linear Prism
- Motorized Iris
- Green/Magenta Shift

GOBOS
- 2x 6 Rotating / Indexing Inter. Glass Gobos
- 1x 7 Fixed Interchangeable Glass Gobos
- Animation Wheel

CONTROL / CONNECTIONS
- 4 DMX Channel Modes
- 16-bit Pan, Tilt, and Dimming Control
- DMX Adjustable LED Frequency
- DMX, RDM Protocol Support
- 4 Button Touch Control Panel

SIZE / WEIGHT
- LxWxH: 462 x 540 x 590 mm (18.2" x 21.3" x 23.2") 462 x 540 x 771 mm (with Snoot) (18.2" x 21.3" x 30.4") (with Snoot)
- Weight: 34.5 kg (76.2 lbs.)

FUZE MAX PROFILE

SOURCE
- 800W 6,500K RGBMA LED Engine
- 30,000 Hour Average LED Life*

PHOTOMETRIC DATA
- 21,000 Total Lumen Output
- CRI 93+

EFFECTS
- 7° - 53° Motorized Zoom
- 4 Rotating Full Blackout Framing Blades, +/- 60° Index
- Dual Variable Frost Filter (Medium/ Wash)
- 4 Facet Round, 4 Facet Linear Prism
- Motorized Iris
- Green/Magenta Shift

GOBOS
- 1x 6 Rotating / Indexing Inter. Glass Gobos
- 1x 7 Fixed Interchangeable Glass Gobos
- Animation Wheel

CONTROL / CONNECTIONS
- 4 DMX Channel Modes
- 16-bit Pan, Tilt, and Dimming Control
- DMX Adjustable LED Frequency
- DMX, RDM Protocol Support
- 4 Button Touch Control Panel

SIZE / WEIGHT
- LxWxH: 462 x 540 x 719 mm (18.2" x 21.26" x 28.3")
- Weight: 34.6 kg (76.3 lbs.)

FUZE WASH 500

SOURCE
- 500W 6,500K RGBMALED Engine
- 30,000 Hour Average LED Life*

PHOTOMETRIC DATA
- 17,000+ Total Lumen Output
- CRI 92+

EFFECTS
- 10° - 45° Motorized Zoom
- Optional Indexable Ovalizer Lens
- Optional 4-Leaf Motorized Barndoor
- CMY Emulation
- Green/Magenta Shift

GOBOS
- N/A

CONTROL / CONNECTIONS
- 4 DMX Channel Modes
- 16-bit Pan, Tilt, and Dimming Control
- DMX Adjustable LED Frequency
- Locking RJ45 Ethernet (Artnet, sACN) In/Out

SIZE / WEIGHT
- LxWxH: 408 x 253 x 540 mm (16.1" x 10.0 x 21.3")
- Weight: 18.5 kg (40.8 lbs.)

FUZE WASH FR

SOURCE
- 480W 6,500K RGBMA LED Engine
- 30,000 Hour Average LED Life*

PHOTOMETRIC DATA
- 15,000+ Total Lumen Output
- CRI 92+

EFFECTS
- 9° - 60° Motorized Zoom
- Variable Frost Filter
- 4 Rotating Full Blackout Framing Blades, +/- 45 Index
- Motorized Iris
- CMY Emulation
- Green/Magenta Shift

GOBOS
- N/A

CONTROL / CONNECTIONS
- 4 DMX Channel Modes
- 16-bit Pan, Tilt, and Dimming Control
- DMX Adjustable LED Frequency
- Locking RJ45 Ethernet (Artnet, sACN) In/Out

SIZE / WEIGHT
- LxWxH: 408 x 256 x 679 mm (16.6" x 10.08 x 26.74")
- Weight: 28.1 kg (62 lbs.)

ELATION PROFESSIONAL

Elation Professional Europe

www.elationlighting.eu

EXTENDED 5 YEARS FIRST LED ENGINE WARRANTY